

Duraseal Floor Polish

Product Description

A clear, pure acrylic floor sealer with superior penetration

A clear, pure acrylic, universal floor emulsion sealer undercoater with superior penetration and adhesion properties. Prolongs and preserves the beauty of new floors and brings out the natural colours in older floors. Its durable protective coat forms a barrier against water, alkaline cleaners, oil and grease. This is an excellent multi purpose acrylic sealer for high or low frequency maintenance.

Typical Uses

Duraseal Floor Polish is designed to protect and preserve the life of floor coverings.

It fills and seals the small openings in porous or “washed out” and worn resilient tiles and prevents dusting and blooming on hard surfaces.

Suitable substrates: May be applied to vinyl, terrazzo, marble, slate, ceramic tiles and floor coatings.

Colour: *Duraseal Floor Polish* is translucent.

Packaging: Supplied in 5 litre units.

Product Benefits

- Provides a perfect foundation for applying topcoat finishes.
- Reduces the number of topcoats needed to produce high gloss and brightness.
- Restores gloss, colour and beauty to worn and dull floors.
- Gives lasting protection against penetration of dirt, water and traffic wear.
- Increases the slip resistance to bare floors.
- Responds to UHS and low speed methods.
- Provides a smooth glossy base film that will not discolour.
- Topcoat finishes are easily removed without affecting the sealer undercoat.
- Frequency of stripping and refinishing is drastically reduced.
- It is essentially odourless, easy to use, adheres well and is recommended for sealing most indoor floor surfaces.

Direction For Use

Preparation

All surfaces must be thoroughly clean, dry and free from loose material.

Application

Application Temperature

Recommended temperature of application is between 10°C and 25°C. Minimum application temperature is 8°C.

Application

1. Thoroughly strip old finish from floors.
2. Rinse with clean water and allow floor to dry thoroughly.
3. Apply 3 to 4 thin coats of sealer, allowing 45-60 minutes drying time between coats. Under humid conditions allow longer drying time (it is important to allow each coat to dry.)

Shelf Life

The shelf life of this product is 2 years, if container is properly resealed after use.

Coverage

140m² - 150m² per 5 litre unit.

Technical Data

Specific Gravity:	1.025
pH:	9.2
Drying time:	45 to 60 minutes at 20°C
Product stability:	Excellent

Cleaning

Tools, equipment etc., should be cleaned immediately after use with water. Use organic hand cleaner for hands.

Health & Safety

Before using this product, please ensure you have received and read carefully both the Hazard Label applied to the container and the relevant Material Safety Data Sheets.

Any Questions

Please do not hesitate to contact us for advice regarding the use of this product or its suitability for your particular application.

Our aim is to provide all the technical help you need to make an informed choice and achieve total success.

Polycote Technical Helpline: **01234 846400**

All reasonable care has been taken in supplying the above information. However, any figures quoted do not constitute a specification but represent typical values obtained. It is the customer's responsibility to ensure the product is fit for the intended purpose and that conditions are suitable. Any technical advice is offered in good faith, but without warranty. This is also applicable when proprietary rights and third parties are involved. In the light of the Company's policy of continual research and development, it is the customer's responsibility to ensure that the information contained herein has not been superseded.