

Duraseal™ Floor Polish

A clear, pure acrylic floor sealer with superior penetration



“maintenance made easy”



PRODUCT DESCRIPTION

A clear, pure acrylic, universal floor emulsion sealer undercoater with superior penetration and adhesion properties. Prolongs and preserves the beauty of new floors and brings out the natural colours in older floors. Its durable protective coat forms a barrier against water, alkaline cleaners, oil and grease. This is an excellent multi purpose acrylic sealer for high or low frequency maintenance.

- **Provides a slip resistant, smooth glossy base film that will not discolour.**
- **Topcoat finishes are easily removed without affecting the sealer undercoat.**
- **Frequency of stripping and refinishing is drastically reduced.**
- **It is essentially odourless, easy to use, adheres well and is recommended for sealing most indoor floor surfaces.**

TYPICAL USES

Duraseal™ Floor Polish is designed to protect and preserve the life of floor coverings.

It fills and seals the small openings in porous or “washed out” and worn resilient tiles and prevents dusting and blooming on hard surfaces.

SUITABLE SUBSTRATES

May be applied to vinyl, terrazzo, marble, slate, ceramic tiles and floor coatings.

COLOUR

Duraseal™ Floor Polish is clear.

PACKAGING

Supplied in 4 litre units.

PHYSICAL & CHEMICAL PROPERTIES

Solids content: 27.8-28.2%

Specific Gravity: 1.035-1.045.

pH: 7.8-8.2

Drying time: 45 to 60 minutes at 20°C

Product stability: Excellent

PRODUCT DESCRIPTION Cont.**PRODUCT BENEFITS:**

- Provides a perfect foundation for applying topcoat finishes.
- Reduces the number of topcoats needed to produce high gloss and brightness.
- Restores gloss, colour and beauty to worn and dull floors.
- Gives lasting protection against penetration of dirt, water and traffic wear.
- Increases the ANTI-SLIP resistance to bare floors.
- Responds to UHS and low speed methods.

POT LIFE:

The minimum pot life of this product is two years if container is properly resealed after use.

COVERAGE:

140m² - 150m² per 4 litre unit.

CLEANING:

Tools, equipment etc., should be cleaned immediately after use with water. Use organic hand cleaner for hands.

DIRECTIONS FOR USE**SURFACE PREPARATION:****THOROUGH SUBSTRATE PREPARATION IS ESSENTIAL.**

All surfaces must be thoroughly clean and dry and free from loose material.

APPLICATION:

1. Thoroughly strip old finish from floors.
2. Rinse with clean water and allow floor to dry thoroughly.
3. Apply 3 to 4 thin coats of sealer allowing 45-60 minutes drying time between coats. Under humid conditions allow longer drying time. (It is important to allow each coat to dry.)

APPLICATION TEMPERATURE:

Recommended temperature of application is between 10°C and 25°C. Minimum application temperature is 8°C.

HEALTH & SAFETY

Before using this product, please ensure you have received and read carefully both the Hazard Label applied to the container and the relevant Material Safety Data Sheets.

ANY QUESTIONS?

Please do not hesitate to contact us for advice regarding the use of this product or its suitability for your particular application.

Our aim is to provide all the technical help you need to make an informed choice and achieve total success.

Polycote Technical Helpline

01234 846400

All reasonable care has been taken in supplying the above information. However, any figures quoted do not constitute a specification but represent typical values obtained. It is the customer's responsibility to ensure for himself that the product is fit for the intended purpose and that conditions are suitable. Any technical advice is offered in good faith, but without warranty. This is also applicable when proprietary rights and third parties are involved. In the light of the Company's policy of continual research and development, it is the customer's responsibility to ensure that the information contained herein has not been superseded.

REV: 06/17