

MATERIAL SAFETY DATA SHEET

350 15 + col. ref

Flortex Flexiset – Part A



"maintenance made easy"

SECTION 1: IDENTIFICATION OF THE SUBSTANCE OR PREPARATION AND THE COMPANY

Product Name: **FLORTEX FLEXISET – PART A**
 Company Name: Polycote UK
 Centre Point • Wolseley Road
 Woburn Road Industrial Estate
 Kempston • Beds MK42 7EF
 Telephone Number: 01234 846400

SECTION 2: HAZARDS IDENTIFICATION

Classification according to Regulation (EC) No. 1272/2008 [CLP]:
 Skin Irrit. 2: H315; Eye Irrit. 2: H319; Skin Sens. 1; H317;
 Aquatic Chronic 2: H411.

Hazard pictograms:



Signal word: Warning

Hazard statements:

H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H411 Toxic to aquatic life with long lasting effects.

Precautionary statements:

P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
 P337 + P313 If eye irritation persists: Get medical advice/attention.
 P101 If medical advice is needed, have product container or label at hand.

Contains: reaction product: bisphenol-A-(epichlorhydrin) oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

Formaldehyde, polymer with (chloromethyl)oxiran and phenol

Supplemental Hazard information (EU):

EUH205 Contains epoxy constituents. May produce an allergic reaction.
 EUH210 Safety data sheet available on request.

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name:

EINECS	CAS No:	Classification	Percent
BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}			
500-033-5	25068-38-6	Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 2: H411	25 - 50%
OXIRANE, MONO[(C12-14-ALKYLOXY)METHYL] DERIVS.			
271-846-8	68609-97-2	Skin Irrit. 2: H315; Skin Sens. 1: H317;	2,5 - 10%
FORMALDEHYDE, POLYMER WITH (CHLOROMETHYL)OXIRAN AND PHENOL			
500-006-8	9003-36-5	Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 2: H411	2,5 - 10%

SECTION 4: FIRST AID MEASURES

General: In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.
 Inhalation: Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.
 Skin contact: Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.
 Eye contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.
 Ingestion: Seek medical advice immediately.
Most important symptoms and effects, both acute and delayed
 No information available.

SECTION 5: FIRE FIGHTING MEASURES

Extinguishing media: Alcohol resistant foam, carbon dioxide, Powder, spray mist, (water).
 Unsuitable media: Strong water jet.
 Exposure hazards: Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.
 Advice for firefighters: Provide a conveniently located respiratory protective device. Do not allow water used to extinguish fire to enter drains, ground or waterways. Treat runoff as hazardous. Cool closed containers that are near the source of the fire.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions: Provide adequate ventilation. See protective measures under point 7 and 8.
 Environmental precautions: Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.
 Methods for cleaning up: Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculite, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see chapter 13). Clean using cleansing agents. Do not use solvents. Disposal considerations: refer to chapter 13.

Polycote Flexiset – Part A Cont.

338 + size ref. + col. ref.

SECTION 7: HANDLING AND STORAGE

- Handling:** Keep container tightly closed and in a well-ventilated place. Protect from heat and direct sunlight.
- Precautions against fire and explosion:** No special fire protection measures are necessary.
- Storage:** Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure – no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Provide for retaining containers, eg. floor pan without outflow. Keep away from strongly acidic and alkaline materials as well as oxidizers. Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15°C and 25°C. Protect from heat and direct sunlight. Keep container tightly closed. Store carefully closed containers upright to prevent any leaks.
- Specific use(s):** Coating material. Observe technical data sheet.

SECTION 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

- DNEL:**
reaction product: bisphenol-A(epichlorhydrin)
DNEL long-term dermal (systemic), Workers: 8,33 mg/kg bw/day
DNEL long-term inhalative (systemic), Workers: 12,25 mg/m³
- Formaldehyde, polymer with (chloromethyl)oxiran and phenol**
DNEL long-term inhalative (systemic), Workers: 29,39 mg/m³
- PNEC:**
reaction product: bisphenol-A(epichlorhydrin)
PNEC aquatic, freshwater: 6 x10⁻³ mg/L
PNEC aquatic, marine water: 6 x10⁻⁴ mg/L
PNEC sediment, freshwater: 6,27 x10⁻² mg/kg wwt
PNEC sediment, marine water: 6,27 x10⁻³ mg/kg wwt
PNEC, Soil: 4,78 x10⁻² mg/kg wwt
PNEC sewage treatment plant (STP): 10 mg/L
- Exposure controls:** Provide good ventilation. This can be achieved with local or room suction.
- Respiratory protection:** Not necessary if room is well-ventilated. During spraying wear suitable respiratory equipment. When spraying, wear self-contained breathing apparatus.
- Hand protection:** For prolonged or repeated handling the following glove material must be used: Butyl caoutchouc (butyl rubber) Thickness of the glove material >0,4 mm. Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.
- Eye protection:** Wear closed protection glasses.
- Protective clothing:** Apron, Boots.
- Protective measures:** After contact clean skin thoroughly with water and soap or use appropriate cleanser.
- Environmental:** Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

SECTION 9: PHYSICAL & CHEMICAL PROPERTIES

- State:** Liquid
- Colour:** Pigmented
- Odour:** Characteristic odour
- Flash point:** >100°C
- Ignition temp:** 230°C
- Relative density:** 1.520 g/cm³
- Solubility:** Insoluble
- pH: at 20°C:** 6.00
- Viscosity at 23°C: ca** 8400 mPa·s
- Solid content (%):** 100,00 Wt %

SECTION 10: STABILITY AND REACTIVITY

- Reactivity:** No information available.
- Chemical stability:** Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to chapter 7.
- Hazardous reactions:** Keep away from strongly acidic and alkaline materials as well as oxidizers. Keep away from amines, alcohols and water.
- Conditions to avoid:** Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to chapter 7. Hazardous decomposition byproducts may form with exposure to high temperatures.
- Haz. decomp. products:** Gases/vapours, irritant.

SECTION 11: TOXICOLOGICAL INFORMATION

- Acute toxicity:**
reaction product: bisphenol-A(epichlorhydrin)
oral, LD50, Rat: 15000 mg/kg
dermal, LD50, Rabbit: 23000 mg/kg
oral, NOAEL(C):, Rat: 50 mg/kg bw/day
dermal, NOAEL(C):, Rabbit: 100 mg/kg bw/day
- Formaldehyde, polymer with (chloromethyl)oxiran and phenol**
oral, LD50, Rat: > 10000 mg/kg
dermal, LD50, Rat: > 2000 mg/kg
oral, NOAEL(C): 250 mg/kg bw/day

Based on the properties of the epoxy constituents and considering toxicological data on similar preparations, this preparation may be a skin sensitiser and an irritant. Preparation contains epoxy-based reactive thinners which are moderately to strongly irritating to eyes, mucous membranes and skin and which are highly sensitizing. Repeated skin contact may result in irritations and sensitizations, possibly due to a cross-over sensitization with other epoxy compounds. Single oral exposure to doses of the epoxy based reactive diluents at or close to the lethal dose has been shown to cause transient neurotoxic effects in animals in some cases. However, uptake through skin and by inhalation has not caused such effects in animals. Prolonged exposure to high concentration may cause adverse effects in target organs such as liver and kidney.

Overall Assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

Polycote UK

Centre Point • Wolsley Road • Woburn Road Industrial Estate
Kempston • Beds • MK42 7EF
Technical Helpline: 01234 846400

SECTION 12: ECOLOGICAL INFORMATION**Overall evaluation:**

There is no information available on the preparation itself.

Do not allow to enter into surface water or drains.

Ecotoxicity:

reaction product: bisphenol-A(epichlorhydrin)

Fish toxicity, LC50, Leuciscus idus (golden orfe): 2 mg/L (96 h)

Daphnia toxicity, EC50, daphnia: 1,8 mg/L (48 h)

Algae toxicity, EC50, Algae: 11 mg/L (72 h)

Formaldehyde, polymer with (chloromethyl)oxiran and phenol

Fish toxicity, LC50, Leuciscus idus (golden orfe): 2,54 mg/L (96 h)

Daphnia toxicity, EC50, daphnia: 2,55 mg/L (48 h)

Algae toxicity, ErC50, Algae: 1,8 mg/L

Results of PBT assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 13: DISPOSAL CONSIDERATIONS

Disposal operations: Do not allow to enter into surface water or drains. Handle contaminated packages in the same way as the substance itself. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

EWC Waste code: 080111 – waste paint and varnish containing organic solvents or other dangerous substances.

Disposal of packaging: Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: TRANSPORT INFORMATION

UN Number: UN3082
UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-A (epichlorhydrin) epoxy resin)
Transport hazard class: 9
Packing group: III
Environmental hazard: Dangerous for the environment
Marine pollutant: p / Bisphenol-A (epichlorhydrin)epoxy resin
Tunnel category: E
EmS-No: F-A, S-F

SECTION 15: REGULATORY INFORMATION**EU legislation:**

according to EU-regulation 2004/42/EC (appendix II)

EU limit value for this product (cat. (Cat. A/i)): 550 g/l (2007)/500 g/l (2010).

This product contains max 500,000 g/l VOC.

National regulations:

Restrictions of occupation:

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

SECTION 16: OTHER INFORMATION**Hazard phrases used**

in s.2 and s.3: H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H411: Toxic to aquatic life with long lasting effects.

All the foregoing information should be regarded as being applicable to the uncured mixed product as well as to the individual components. This material may form part of a multi component pack, and is supplied in the correct proportions for that pack. Please check all of the product labels to ensure that the correct components and pack sizes are being used. Select and use appropriate pack sizes to minimise waste and operator exposure, do not split packs. Use in batch order.

The Safety Data above is applicable to the product only as used according to the purposes and methods described on the relevant Technical Data Sheet, available from Polycote UK on request. The information above is based on our present knowledge and is believed to be correct but does not purport to be all inclusive and should only be used as a guide. No warranty is implied with respect to the specification of the product. It is intended to describe the product solely in terms of its safety requirements and relates only to the specific material designed and may not be valid for such material used in combination with any other materials or in any process. This data does not constitute the users own assessment of workplace risk as required by other Health and Safety legislation, nor is it a sales specification or indication of suitability for any particular use. The user must satisfy himself as to the suitability of the product for his purpose. No legally valid contractual relationship is established by the above data, and Polycote UK shall not be held liable for any damage resulting from handling or from contact with the above product.

Date of Issue: July 2015

Polycote UK

Centre Point • Wolsley Road • Woburn Road Industrial Estate

Kempston • Beds • MK42 7EF

Technical Helpline: 01234 846400



"maintenance made easy"

MATERIAL SAFETY DATA SHEET

350 15 + col. ref

Flortex Flexiset – Part B



SECTION 1: IDENTIFICATION OF THE SUBSTANCE OR PREPARATION AND THE COMPANY

Product Name: **FLORTEX FLEXISET – PART B**
 Company Name: Polycote UK
 Centre Point • Wolseley Road
 Woburn Road Industrial Estate
 Kempston • Beds MK42 7EF
 Telephone Number: 01234 846400

SECTION 2: HAZARDS IDENTIFICATION

Classification according to Regulation (EC) No. 1272/2008 [CLP]:
 Acute Tox. 4: H302; Skin Corr. 1B: H314; Skin Sens. 1:
 H317; Aquatic Chronic 3; H412.

Hazard pictograms:



Signal word: Danger

Hazard statements:

H302 Harmful if swallowed.
 H314 Causes severe skin burns and eye damage.
 H317 May cause an allergic skin reaction.
 H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P260 Do not breathe vapour.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

Contains:

benzyl alcohol
 poly(oxypropylen)diamine
 Formaldehyde, oligomeric reaction products with 3,3'-iminodi(propylamine)

Supplemental Hazard information (EU):

EUH210 Safety data sheet available on request.

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name:

EINECS	CAS No:	Classification	Percent
BENZYL ALCOHOL			
202-859-9	100-51-6	Acute Tox. 4: H332; Acute Tox. 4: H302	25 - 50%
POLY(OXYPROPYLEN)DIAMINE			
618-561-0	9046-10-0	Skin Corr. 1C H314; Eye Dam. 1: H318; Asp. Tox. 1: H304; Aquatic Chronic 2: H411	25 - 50%
FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH 3,3'-IMINODI(Propylamine)			
500-626-9	161278-35-9	Acute Tox. 4: H302; Skin Corr. 1B: H314; Eye Dam. 1: H318; Skin Sens. 1: H317	25 - 50%
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT			
265-149-8	64742-47-8	Asp. Tox. 1 H304	1 - 2,5%

SECTION 4: FIRST AID MEASURES

General: In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

Inhalation: Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Skin contact: Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

Eye contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Ingestion: If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed
 No information available.

SECTION 5: FIRE FIGHTING MEASURES

Extinguishing media: Alcohol resistant foam, carbon dioxide, Powder, spray mist, (water).

Unsuitable media: Strong water jet.

Exposure hazards: Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

Advice for firefighters: Provide a conveniently located respiratory protective device. Do not allow water used to extinguish fire to enter drains, ground or waterways. Treat runoff as hazardous. Cool closed containers that are near the source of the fire.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions: Provide adequate ventilation. See protective measures under point 7 and 8.

Environmental precautions: Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

Methods for cleaning up: Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculite, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see chapter 13). Clean using cleansing agents. Do not use solvents. Disposal considerations: refer to chapter 13.

Polycote Flexiset – Part B Cont.

338 + size ref. + col. ref.

SECTION 7: HANDLING AND STORAGE

- Handling:** Keep container tightly closed and in a well-ventilated place. Protect from heat and direct sunlight.
- Precautions against fire and explosion:** No special fire protection measures are necessary.
- Storage:** Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSIVO). Keep container tightly closed. Do not empty containers with pressure – no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Provide for retaining containers, eg. floor pan without outflow. Keep away from strongly acidic and alkaline materials as well as oxidizers. Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15°C and 25°C. Protect from heat and direct sunlight. Keep container tightly closed. Store carefully closed containers upright to prevent any leaks.

SECTION 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

- DNEL:**
benzyl alcohol
DNEL long-term inhalative (local), Workers: 90 mg/m³
DNEL long-term inhalative (systemic), Workers: 90 mg/m³
- poly(oxypropylen)diamine
DNEL long-term dermal (local), Workers: 0,623 mg/cm²
DNEL long-term dermal (systemic), Workers: 2,5 mg/kg bw/day
- PNEC:**
poly(oxypropylen)diamine
PNEC aquatic, freshwater: 1,5 x10⁻² mg/L
PNEC aquatic, marine water: 1,43 x10⁻² mg/L
PNEC aquatic, intermittent release: 0,15 mg/L
PNEC sediment, freshwater: 0,132 mg/kg
PNEC sediment, marine water: 0,125 mg/kg
PNEC, Soil: 1,76 x10⁻² mg/kg
PNEC sewage treatment plant (STP): 7,5 mg/L
PNEC Secondary Poisoning: 6,93 mg/kg
- Exposure controls:** Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.
- Respiratory protection:** Not necessary if room is well-ventilated. During spraying wear suitable respiratory equipment. When spraying, wear self-contained breathing apparatus.
- Hand protection:** For prolonged or repeated handling the following glove material must be used: Butyl caoutchouc (butyl rubber) Thickness of the glove material >0,4 mm. Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.
- Eye protection:** Wear closed protection glasses.
- Protective clothing:** Apron, Boots.
- Protective measures:** After contact clean skin thoroughly with water and soap or use appropriate cleanser.
- Environmental:** Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

SECTION 9: PHYSICAL & CHEMICAL PROPERTIES

- State:** Liquid
Colour: Amber
Odour: Characteristic odour
Flash point: >100°C
Ignition temp: 300°C
Relative density: 1.006 g/cm³
Solubility: Insoluble
pH: at 20°C: 9.00
Viscosity at 23°C: ca 120 mPa·s
Solid content (%): 98,59 Wt %

SECTION 10: STABILITY AND REACTIVITY

- Reactivity:** No information available.
Chemical stability: Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to chapter 7.
Hazardous reactions: Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.
Conditions to avoid: Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to chapter 7. Hazardous decomposition byproducts may form with exposure to high temperatures.
Haz. decomp. products: Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

- Classification for mixtures and used evaluation method according to regulation (EC) 1207/2008 [CLP].
No data on preparation itself available.

Overall Assessment on CMR properties

- The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

SECTION 12: ECOLOGICAL INFORMATION

- Overall evaluation:**
Classification for mixtures and used evaluation method according to regulation (EC) 1207/2008 [CLP].
There is no information available on the preparation itself.
Do not allow to enter into surface water or drains.
Results of PBT assessment
The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

Polycote UK

Centre Point • Wolsley Road • Woburn Road Industrial Estate
Kempston • Beds • MK42 7EF
Technical Helpline: 01234 846400

Polycote Flexiset – Part B Cont.

338 + size ref. + col. ref.

SECTION 13: DISPOSAL CONSIDERATIONS

Disposal operations: Do not allow to enter into surface water or drains. Handle contaminated packages in the same way as the substance itself. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

EWC Waste code: 080111 – waste paint and varnish containing organic solvents or other dangerous substances.

Disposal of packaging: Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: TRANSPORT INFORMATION

UN Number: UN1760
 UN proper shipping name: CORROSIVE LIQUID, N.O.S.
 (Poly(oxypropylene)diamine,
 Formaldehyde, reaction products w.
 3,3'-iminodi(propylamine))

Transport hazard class: 8
 Packing group: III
 Environmental hazard: n.a.
 Marine pollutant: n.a.
 Tunnel category: E
 EmS-No: F-A, S-B

SECTION 15: REGULATORY INFORMATION

EU legislation:
 according to EU-regulation 2004/42/EC (appendix II)
 EU limit value for this product (cat. (Cat. A/i)): 550 g/l (2007)/500 g/l (2010).
 This product contains max 500,000 g/l VOC.

National regulations:
 Restrictions of occupation:
 Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
 Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

SECTION 16: OTHER INFORMATION

Hazard phrases used
 in s.2 and s.3: H302: Harmful if swallowed.
 H304: May be fatal if swallowed and enters airways.
 H314: Causes severe skin burns and eye damage.
 H317: May cause an allergic skin reaction.
 H318: Causes severe eye damage.
 H332: Harmful if inhaled.
 H411: Toxic to aquatic life with long lasting effects.

All the foregoing information should be regarded as being applicable to the uncured mixed product as well as to the individual components. This material may form part of a multi component pack, and is supplied in the correct proportions for that pack. Please check all of the product labels to ensure that the correct components and pack sizes are being used. Select and use appropriate pack sizes to minimise waste and operator exposure, do not split packs. Use in batch order.

The Safety Data above is applicable to the product only as used according to the purposes and methods described on the relevant Technical Data Sheet, available from Polycote UK on request. The information above is based on our present knowledge and is believed to be correct but does not purport to be all inclusive and should only be used as a guide. No warranty is implied with respect to the specification of the product. It is intended to describe the product solely in terms of its safety requirements and relates only to the specific material designed and may not be valid for such material used in combination with any other materials or in any process. This data does not constitute the users own assessment of workplace risk as required by other Health and Safety legislation, nor is it a sales specification or indication of suitability for any particular use. The user must satisfy himself as to the suitability of the product for his purpose. No legally valid contractual relationship is established by the above data, and Polycote UK shall not be held liable for any damage resulting from handling or from contact with the above product.

Date of Issue: July 2015

Polycote UK

Centre Point • Wolsley Road • Woburn Road Industrial Estate
 Kempston • Beds • MK42 7EF
 Technical Helpline: 01234 846400

POLYCOTE®
“maintenance made easy”