Product Group: 430

Page: 1 of 1 CL/SfB (43)

PVC Floor Marking Tapes

Industrial tape with super strong adhesive



"maintenance made easy"



PRODUCT DESCRIPTION

Polycote's Floor Marking Tapes are heavy duty plasticised PVC tapes that provide instant demarcation lines for gangways and restricted areas.

TYPICAL USES

Floor Marking Tapes are ideal for use in sports halls, warehouses, hospitals etc.

COLOUR

The Floor Marking Tapes come in a range of colours including, black, yellow, red, white, green and blue. Hazard colours are red/white, black/yellow and white/green.

wnite/green.

PACKAGING

Floor Marking Tapes come in rolls of 33m in either

50mm or 100mm widths.

APPLICATION GUIDE

SURFACE PREPARATION

A clean, dry surface is essential. It is important to ensure that all surface contaminants (paint flakes, oil, grease, dust, etc) are removed.

TAPE APPLICATION

Make sure the tape is applied within the recommended temperature range. Apply the tape using the maximum amount of pressure possible, smoothing down to achieve 100% contact.

TECHNICAL DETAILS

Tape Thickness:	0.15mm
Tensile Strength at Break:	28.0 N/10mm
Elongation at Break:	150%
Adhesion to Steel:	2.0 N/10mm
Adhesion to Self:	2.0 N/10mm
pH	6.0 to 8.0
Conductivity:	Max 2.5 mS/m
Service Temperature:	0°C to 60°C
Service Temperature: Application Temperature:	0°C to 60°C 5°C to 40°C
<u> </u>	
Application Temperature:	
Application Temperature: Recommended	5°C to 40°C

ANY QUESTIONS?

Polycote Technical Helpline:

01234 846400

All reasonable care has been taken in supplying the above information. However, any figures quoted do not constitute a specification but represent typical values obtained. It is the customer's responsibility to ensure for himself that the product is fit for the intended purpose & that conditions are suitable. Any technical advice is offered in good faith, but without warranty. This is also applicable when proprietary rights & third parties are involved. In the light of the Company's policy of continual research & development, it is the customer's responsibility to ensure that the information contained herein has not been superseded.

REV: 01/18

Polycote UK

Centre Point · Wolseley Road · Woburn Road Industrial Estate

Kempston • Beds • MK42 7EF Technical Help line: 01234 846400



"maintenance made easy"