



# Technical Data Sheet

## Graffiti Remover Liquid

### Graffiti Remover Liquid

#### Product Description

Acid-based formulation for easy removal of graffiti

*Graffiti Remover Liquid* is a high strength inorganic acid solution containing corrosion inhibitors and wetting agents. An extremely effective yet safe acid, it is designed to dissolve or break down paint, ink, markers, and other substances used in graffiti as well as ensuring an effective surface key to improve the adherence of paint or other coatings.

#### Typical Uses

*Graffiti Remover Liquid* will remove paint, ink, dirt, grime, diesel oil, food oil, fats, grease, engineering oil, tobacco film and rubber marks from all types of walls and virtually any other hard surfaces and even fabrics. It is widely used for regular cleaning routines on plant equipment and machinery, boats and many industrial food sites, engineering, warehousing, commercial, hospital and school applications.

**Suitable substrates:** *Graffiti Remover Liquid* may be applied to concrete, quarry and ceramic tiles, terrazzo, brick and metal.

**Colour** *Graffiti Remover Liquid* is a clear colourless liquid.

**Packaging:** *Graffiti Remover Liquid* is supplied in 1 litre units.

#### Direction For Use

##### Surface Preparation

Use a stiff brush to remove all flaking paint and loose friable material before application of *Graffiti Remover Liquid*

##### Mixing

Mix thoroughly before use.

##### Application

Using a brush, soft broom, sponge, spray, mop or cloth as appropriate, soak the area with the liquid. Allow between 5 and 10 minutes for acid to penetrate, then **RINSE THOROUGHLY** with water.

##### Application Temperature

Normal application temperature is between +5°C and +30°C.

##### Coverage

The coverage per litre of *Graffiti Remover Liquid* is 5-6m<sup>2</sup>. The coverage depends greatly on the condition of the surface.

#### Shelf Life & Storage

*Graffiti Remover Liquid* may be stored indefinitely without deterioration subject to conditions being cool, dry and frost-free.

#### Health & Safety

Before using this product, please ensure you have received and read carefully both the Hazard Label applied to the container and the relevant Material Safety Data Sheets.

#### Any Questions

Please do not hesitate to contact us for advice regarding the use of this product or its suitability for your particular application.

Our aim is to provide all the technical help you need to make an informed choice and achieve total success.

Polycote Technical Helpline: **01234 846400**

All reasonable care has been taken in supplying the above information. However, any figures quoted do not constitute a specification but represent typical values obtained. It is the customer's responsibility to ensure the product is fit for the intended purpose and that conditions are suitable. Any technical advice is offered in good faith, but without warranty. This is also applicable when proprietary rights and third parties are involved. In the light of the Company's policy of continual research and development, it is the customer's responsibility to ensure that the information contained herein has not been superseded.